PATENT
ATTORNEY DOCKET LI 2 RE

10/C

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Patent Number: RE39028

Patentees: Ming-Jun Li, et al

Serial No: 10/086222

Filed: February 27, 2002

For: HIGH PERFORMANCE SINGLE MODE WAVEGUIDE

Group Art Unit: 2883

Examiner: Healy, Brian M



**REQUEST FOR CERTIFICATE OF CORRECTION FOR**

***PTO MISTAKE PURSUANT TO 35 U.S.C. § 254 AND 37 C.F.R. § 1.322***

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

This is a request for the issuance of a Certificate of Correction in the above-identified patent. Two (2) copies of Form PTO 1050 are appended. The corrections involve the bibliographic (cover) page and pages 7 and 8.

The mistakes identified in the appended Form occurred through the fault of the Patent Office, as clearly disclosed by the records of the application which matured into this patent.

Issuance of the Certificate of Correction is requested.

Respectfully submitted,

CORNING INCORPORATED

Robert L. Carlson
Registration No.: 35,473
Phone: 607-974-3502
Date: April 17, 2006

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to Commissioner of Patents, P.O. Box 1450, Alexandria, VA 223131-1450 on

April 17, 2006
Date of Deposit

Signature

(Also Form PTO-1050)

**UNITED STATES PATENT AND TRADEMARK OFFICE**

***CERTIFICATE OF CORRECTION***

PATENT NO. : RE39028
DATED : March 21, 2006
INVENTOR(S) : Ming-Jun Li, et al

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

| *No.* | *Col.* | *Line* | *Description* |
|---|---|---|---|
| **1** | Abstract | 1 | "Disclosed is a single made optical waveguide fiber having a"—should be—"Disclosed is a single mode optical waveguide fiber having a" |
| **2** | 7 | 10 | "radius $r_3$ and a second annular segment surrounding, and"—should be—"radius $r_1$ and a second annular segment surrounding, and" |
| **3** | 7 | 32 | "in the range 2.06 μm to 2.80 μm $r_1$ is in the range 455 μm"—should be—" in the range 2.06 μm to 2.80 μm $r_1$ is in the range 4.55 μm" |
| **4** | 7 | 41 | "**5**. The single mode waveguide of claim 1 is which the"—should be—"**5**. The single mode waveguide of claim 1 in which the" |
| **5** | 7 | 66 | "profile having or about equal to 1, the index profile of"—should be—"profile having $\alpha$ about equal to 1, the index profile of" |
| **6** | 8 | 61 | "posing an induced loss under pin array bend testing of less"—should be—"prising an induced loss under pin array bend testing of less" |
| **7** | 9 | 2 | "posing a dispersion at 1530 nm which is greater than 1"—should be—"prising a dispersion at 1530 nm which is greater than 1" |
| **8** | 10 | 7 | "1530 nm, to 1565 nm which is positive and no greater than"—should be—"1530 nm to 1565 nm which is positive and no greater than" |

MAILING ADDRESS OF SENDER

Corning Incorporated
SP-TI-3-1
Corning, NY 14831

PATENT NO. RE39028

No. of additional copies 1

APR 24 2006

(Also Form PTO-1050)

**UNITED STATES PATENT AND TRADEMARK OFFICE**

***CERTIFICATE OF CORRECTION***

PATENT NO. : RE39028
DATED : March 21, 2006
INVENTOR(S) : Ming-Jun Li, et al

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

| *No.* | *Col.* | *Line* | *Description* |
|---|---|---|---|
| **1** | Abstract | 1 | "Disclosed is a single made optical waveguide fiber having a"—should be—"Disclosed is a single mode optical waveguide fiber having a" |
| **2** | 7 | 10 | "radius $r_3$ and a second annular segment surrounding, and"—should be—"radius $r_1$ and a second annular segment surrounding, and" |
| **3** | 7 | 32 | "in the range 2.06 μm to 2.80 μm $r_1$ is in the range 455 μm"—should be—" in the range 2.06 μm to 2.80 μm $r_1$ is in the range 4.55 μm" |
| **4** | 7 | 41 | "**5**. The single mode waveguide of claim 1 is which the"—should be—"**5**. The single mode waveguide of claim 1 in which the" |
| **5** | 7 | 66 | "profile having or about equal to 1, the index profile of"—should be—"profile having $\alpha$ about equal to 1, the index profile of" |
| **6** | 8 | 61 | "posing an induced loss under pin array bend testing of less"—should be—"prising an induced loss under pin array bend testing of less" |
| **7** | 9 | 2 | "posing a dispersion at 1530 nm which is greater than 1"—should be—"prising a dispersion at 1530 nm which is greater than 1" |
| **8** | 10 | 7 | "1530 nm, to 1565 nm which is positive and no greater than"—should be—"1530 nm to 1565 nm which is positive and no greater than" |

MAILING ADDRESS OF SENDER

Corning Incorporated
SP-TI-3-1
Corning, NY 14831

PATENT NO. RE39028

No. of additional copies 1

APR 24 2006